mulch, mulch shall be anchored by an approved 3 existing parking spaces to be delineated for proposed used car sales display area method ? erosion & sedimentation control measures shall be installed prior to construction & removed as soon os lhey are no longer necessary s landscaping molerials will be maintained in a healthy condition, any material that dies shall 16 be rebloced 4 all exterior lighting shall be directed loward the interior of the site & away from the adjocent properties and West liet a Good B. Oubrey Hullman & Ossoc. 5 pave specs: base to be aggs, moli sign et = 210 compact to a depth of to inches will prime and double seal N2U°51'50"W 10U.8U surface treatment (intirim pave . see note 8 below) le all dimensions shown are to the face of curbs & walks and to the outside margins of building walls unless engineering and shown and noted otherwise. Woler & Sewer Service Shall be supplied by the albemorte County Service Outhority all materials & methods of 01510 (490) · @ /kgp) parking (A) construction shall comply with the olds & specs of the handicapped parking space 12'1 (14p) 8. permonent pove specs. (see note \$5 above for interim pove specs.) surface to be 165 lbs./ squd bil conc lype 5.5 to be placed offer interim pove has settled at least one year. 203. curb to be KG1-2 DUET SIG CUITE 0 @ @ @ , 6 Company of the party of the company 526° 43' 05"E 164.71 exist entrance WALL 9 woler area of 15 saving y Service intermittent parking within Plan Scole: 1" = 20' designated scale in Ree travelway; staff recommend pavement striping, curb painting, and/or "no parking" signage