October 18, 2018

Revised: March 12, 2019 Revised: April 29, 2019 Revised: June 3, 2019

#### ZMA2018-13 Rio Road West

### **Code of Development**

The following is a Code of Development drafted in accordance with Sec.20A.5 of Chapter 18 of the Code of Albemarle; this Code of Development is specific to tax map parcels 45-101, 45-101B, 45-100A, and 45-100 in Albemarle County. This Code of Development establishes the unifying design guidelines, specific regulations, and block characteristics of this Neighborhood Model District. The COD also provides certainty about the permitted uses, locations and appearance of central features.

### I. Table of Uses by Block (Section 20A.5a)

The table below establishes the permitted residential and non-residential uses, special uses and prohibited uses by block.

"P" = "Permitted"

"SP" = "Special Use Permit"

"N" = "Not Permitted"

Table A. Uses: By Right, by Special Permit and Not Permitted
Restrictions & Requirements Associated with standards in the table:
Mixed uses (residential and commercial) are allowed in Blocks 1 and 2.

Table A. Uses: By Right, by Special Permit, and Not Permitted					
BLOCK	BLOCK 1	BLOCK 2	BLOCK 3		
	Active Urban	Neighborhood Services & Local Manufacturing	Neighborhood Greenspace		
Residential					
Single Family Attached/Townhouses	SP	SP	N		
Multifamily	Р	Р	N		
Non- Residential					
Retail (Neighborhood, Community, Regional)	Р	Р	N		
General Commercial Service	Р	Р	N		

Office / R&D / Flex	Р	Р	N
Light Industrial / Self-Storage / Distribution	SP	Р	N
Auto Commercial Sales & Service	SP	Р	N
Institutional	Р	Р	N
Parking Facilities/Structured Parking	Р	Р	N
Water, sewer, energy and communications distribution facilities	Р	Р	Р
Accessory uses and buildings including storage buildings	Р	Р	Р
Temporary construction headquarters and temporary construction storage yards (reference 5.1.18)	Р	Р	Р
Public uses (reference 5.1.12)	Р	Р	Р
Group Homes	Р	Р	N
Tier I and Tier II personal wireless service facilities (reference 5.1.40)	Р	Р	Р
Outdoor storage, display and/or sales serving or associated with a permitted use, other than a residential use	N	SP	N
Greenspace and Amenities	Р	Р	Р

#### Notes to Table A:

- 1.) Reference to uses not otherwise defined or listed in this Code of Development shall be defined as listed first, in the Albemarle County Zoning Ordinance or second, in the adopted Comprehensive Plan. If no definition of the use is provided in any of the three noted documents (Code of Development, Zoning Ordinance, Comprehensive Plan) then such use must be officially determined by the zoning administrator to be permitted in a particular Block pursuant to subsection 8.5.5.2(c)(1).
- 2.) Accessory uses in Block 3 shall be accessory to the recreational use of the block

## II. Use Requirements and Restrictions (Section 20A.5.e)

Uses and buildings permitted within the neighborhood greenspace shall be accessory to recreational use

Hotels, motels, and inns shall be considered general commercial service use.

### III. Prohibited Uses (Section 20A.5.f)

The following are prohibited uses within the NMD:

- All uses expressly provided for in Sec. 26.2(d) of the Albemarle County Code.
- Single Family Detached Residential

# IV. Development Square Footage Proposed and Residential Density (Section 20A.5b & c)

Table B. Density, Housing Type and Non-Residential Use by Block							
Block	Approximate Block Size	MIN Dwelling Units	MAX Dwelling Units	MAX Block Gross Density	Permitted Housing Types	MIN Non- Residential SF	MAX Non- Residential SF
Block 1	64,033 SF			_			
Active Urban	1.47 Ac	30	112	80 DUA	Multifamily, Group Homes	0	290,900
Block 2	56,628 SF						
Neighborhood Services & Local Manufacturing	1.3 Ac	0	62	47.7 DUA	Multifamily, Group Homes	0	310,000
Block 3	23,958 SF						
Neighborhood Greenspace	.55 ac	0	0	0	Not Permitted	0	600
TOTAL	3.32 Ac	30	112	33.7 DUA		0	601,500

#### Notes to Table B:

- 1.) Non-residential square footage allowed in neighborhood greenspace to accommodate structures such as picnic pavilions and buildings accessory to the recreational use of the block.
- 2.) 15% of the residential units built within the NMD will be designated as affordable for a period of 10 years from the date of issuance of certificate of occupancy. The units will rent at a rate making them affordable to those making no more than 80% of Albemarle County's median family income. The monthly rental rate shall not exceed 30% of the monthly gross income of a family making 80% of Albemarle County's median family income. The property owner shall maintain records documenting the household income of the occupants of the affordable units; and upon request by the County, the property owner shall provide the County with these records.

If the residential units with the NMD are built incrementally, one affordable unit shall be provided for every seven market rate units built.

# V. Green Space & Amenities (Section 20A.5d)

The table below establishes green space and amenities provided by block. The Greenspace provided in Block III is within the Amenity Area. The Amenity Area in Block III is to be outdoor, ground story open space.

Table C. Minimum Green Space and Amenities by Block

Table C. Minimum Green Space and Amenities by Block			
BLOCK	Amenity Area MIN	Green Space Area MIN	Green Space Elements
Block 1 Active Urban	0	0	Landscaping and Screening in accordance with Sec. 32.7.9 of the Albemarle County Code
Block 2  Local  Manufacturing &  Neighborhood  Services	0	0	Landscaping and Screening in accordance with Sec. 32.7.9 of the Albemarle County Code
Block 3  Neighborhood Greenspace	.55 Acre	.5 Acre	Designed Landscape including Canopy Cover and Understory, Landscaping and Screening in accordance with Sec. 32.7.9 of the Albemarle County Code
% of total area	16.5%	15%	

# a.) Parking Standards

Parking provided on site shall comply with regulations outlined in Sec. 4.12.6 of the Albemarle County Zoning Ordinance unless the use is expressly provided for in the table below:

Type of Land Use	Parking Space Required for Each:		
	Minimum	Maximum	
Residential			
Single Family Attached/Townhouses	.5 per unit	2 per unit	
Multifamily, any unit of 500 square feet or less	None required	1 per unit	
Multifamily, one (1) bedroom	None required	2 per unit	
Multifamily, two or more bedrooms	None required	3 per unit	
Non-Residential			
Retail	1 per 500 sq. ft. plus 1 per 2 employees on shift	1 per 150 sq. ft. plus 1 per employee on shift	
General Commercial Service	1 per 500 sq. ft. plus 1 per 2 employees on shift	1 per 150 sq. ft. plus 1 per employee on shift	
Office / R&D / Flex	1 per 500 sq. ft.	1 per 150 sq. ft.	
Light Industrial / Distribution	1 per 5,000 sq. ft. plus 1 per 2 employees on shift	1 per 1,000 sq. ft. plus 1 per employee on shift	
Self-Storage Facility	1 per 100 units plus 1 per 2 employees on shift	1 per 50 units plus 1 per every employee on shift	
Auto Commercial Sales & Service	1 per 5,000 sq. ft. of indoor showroom area plus 1 per 2 employees on shift	1 per 1,500 sq. ft. of indoor showroom area plus 1 per employee on shift	

- 1.) When calculating parking totals, the number of parking spaces required shall be rounded up to the nearest whole number.
- 2.) Parking minimums and maximums may be waived or modified upon request by the developer and approval by the zoning administrator. Developer requests for parking reductions shall be made in accordance with Sec. 4.12.2.c(1) of the Albemarle County Zoning Ordinance.

# VI. Architectural Standards (Section 20A.5g)

The form of the building and proportions of structures shall be informed by the lot and building regulations provided for within this code of development.

Architectural design and detail of structures visible from the Entrance Corridor shall be subject to Sec. 30.6 "Entrance Corridor Overlay District" of the Albemarle County Code.

Buildings within the NMD shall feature active facades, with greatest attention given to those facades fronting on an entrance corridor and the proposed greenway. An active façade shall be defined as follows:

- Stepbacks as required by Table D
- Ground floor transparency as required by Table D
- Variation in materials
- Façade breaks (projections, recesses)
- Architectural detailing and elements such as: canopies, balconies, water tables, string courses, cornices, varying roof forms, etc.

#### Historic Resources

There are no designated historic sites or structures on the property.

### VII. Landscape Treatment (Section 20A.5h)

Landscaping and screening shall be provided in accordance with Sec. 32.7.9 of the Albemarle County Code.

### Additional Landscape Requirements:

Block II: The rear of Block II adjacent to Block III shall feature medium or large trees appropriate for the planting conditions at a minimum spacing of 30'

# VIII. Lot & Building Height Regulation (Section 20A.5i)

Table D. Lot & Building Regulation

BLOCK 1  Active Urban  Neighborhood Services & Locate Manufacturing  Building Height  Stories  Primary  3 Min.— 6 Max.  2 Min.— 6 Max.  1 Max  Ground Floor to Floor  Front  2' min.— 12' max.  Side  0'  0' Min.  Rear  0'  0' Min.  To' Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  Frontage Build-out  70% min.  N/A  N/A  N/A  N/A  N/A  N/A  Other  Allowable Building SF  Front Façade: residential: 30%; commercial: 30%; commercial: 15%  All Other Facades: Residential: none required Commercial: 50'  Min Distance  Between Ground Floor Pedestrian Entrances  Neidential: 100'; commercial 50'  Power of the services & Locate Manufacturing  Neighborhood Greenspace  Neighborhood Greenspace  Nima Max  1 Max  1 Max  1 Max  1 Max  1 Max  1 Min Min Min Min N/A  N/A  10' min.— 30' max.  N/A  Minimum 15' after the 4th Floor Ceiling Height of 50' Vertical Height (see note 3)  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/	Table D. Lot and Building Regulations					
Building Height Stories  Primary 3 Min.—6 Max. 2 Min.—6 Max. 1 Max  Ground Floor to Floor  Setbacks  Front 2' min.—12' max. N/A 10' min.—30' max.  Side 0' 0' Min. 5' min.  Rear 0' 0' 0' Min. 5' min.  Rear 0' 0' 0' 15' min.  Rear 0' No' No' Vertical Height or 50' Min. N/A		BLOCK 1	BLOCK 2	BLOCK 3		
Primary 3 Min.— 6 Max. 2 Min.— 6 Max. 1 Max  Ground Floor to Floor 14' Min. 9' Min N/A  Setbacks  Front 2' min. — 12' max. N/A 10' min. — 30' max.  Side 0' 0' Min. 5' min.  Rear 0' 0' 0' 15' min.  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  Frontage Build-out 70% min. N/A N/A  Other  Allowable Building SF  Ground Floor Transparency MIN  Rear Façade: Residential: 10% commercial: 15%  All Other Facades: Residential: 10% commercial: 15%  All Other Facades: Residential: none required Commercial: none required  MIN Distance Between Ground Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  MIN Distance Residential 100'; commercial 50' residential 100'; commercial 50'		Active Urban	Services & Local			
Primary 3 Min.— 6 Max. 2 Min.— 6 Max. 1 Max  Ground Floor to Floor 14' Min. 9' Min N/A  Setbacks  Front 2' min.— 12' max. N/A 10' min.— 30' max.  Side 0' 0' Min. 5' min.  Rear 0' 0' 15' min.  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  Frontage Build-out 70% min. N/A N/A  Other  Allowable Building 290,900 310,000 600  Front Façade: residential: 30%; commercial 60%  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required Commercial: none required Tequired Commercial: none required Commercial: 50' commercial 50' residential 100'; commercial 50'	Building Height					
Ground Floor to Floor  Setbacks  Front 2' min. – 12' max. N/A 10' min. – 30' max.  Side 0' 0' Min. 5' min.  Rear 0' 0' 0' 15' min.  Stepbacks  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical	Stories					
Setbacks  Front 2' min. – 12' max. N/A 10' min. – 30' max.  Side 0' 0' Min. 5' min.  Rear 0' 0' 0' 15' min.  Stepbacks Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  Frontage Build-out 70% min. N/A N/A  Other Allowable Building SF  Ground Floor Transparency MIN Rear Façade: Residential: 30%; commercial 50' commercial: 10% Commercial: none required Commercial: none required Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian residential 100'; commercial 50' residential 100'; commercial 50' commercial 50'	Primary	3 Min 6 Max.	2 Min.– 6 Max.	1 Max		
Front 2' min. – 12' max. N/A 10' min. – 30' max.  Side 0' 0' Min. 5' min.  Rear 0' 0' 0' 15' min.  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  Frontage Build-out 70% min. N/A N/A  Other  Allowable Building SF 290,900 310,000 600  Front Façade: residential: 30%; commercial 60% commercial 30%  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: 10% commercial: 15%  All Other Facades: Residential: none required Commercial: none required required required required For Pedestrian  MIN Distance Between Ground Floor Pedestrian residential 100'; commercial 50' residential 100'; commercial 50'		14' Min.	9' Min	N/A		
Side 0' 0' Min. 5' min.  Rear 0' 0' 15' min.  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  Frontage Build-out 70% min. N/A N/A  Other  Allowable Building SF  Ground Floor Transparency MIN  All Other Facade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required Commercial: none required Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  Min Distance Stephacks  Min Distance Between Ground Floor Pedestrian  Min Distance Between Ground Floor Pedestrian  Min Distance Stephacks Or Distance Pedical Ste	Setbacks					
Rear  O'  O'  Ninimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  Frontage Build-out  Other  Allowable Building SF  Ground Floor Transparency MIN  All Other Facade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required Commercial: none required Floor Pedestrian  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  N/A  N/A  N/A  N/A  N/A  N/A  Rear Façade: Front Façade: residential: 30%; commercial 30%  Rear Façade: Residential: 10% commercial: 15%  All Other Facades: Residential: none required Commercial: none required C	Front	2' min. – 12' max.	N/A	10' min. – 30' max.		
Stepbacks  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height or 50' Vertical Height (see note 3)  Frontage Build-out  Other  Allowable Building SF  Front Façade: residential: 30%; commercial 60%  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required  Commercial: none required  MIN Distance Between Ground Floor Pedestrian  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height (see note 3)  N/A  N/A  N/A  N/A  N/A  N/A  Front Façade: residential: 30%; commercial 30%  Rear Façade: Rear Façade: residential: 10% commercial: 15%  All Other Facades: Residential: none required  Commercial: none required  Commercial: none required  Transparency MIN  N/A  N/A  N/A  All Other Facade: Rear Façade: residential: 10% commercial: 15%  Commercial: 15%  Transparency MIN  Rear Façade: residential: 10% commercial: 10% commercial: 15%  N/A  All Other Facades: Residential: none required  Commercial: none required  Commercial: none required  Transparency MIN  N/A  N/A  N/A  Pront Façade: residential: 30%; commercial: 10% commercial: 50'	Side		0' Min.	5' min.		
Stepbacks  Minimum 15' after the 4th Floor Ceiling Height or 50' Vertical Height or 50' Vertical Height (see note 3)  Frontage Build-out  Other  Allowable Building SF  Front Façade: residential: 30%; commercial 60%  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required  Commercial: none required  MIN Distance Between Ground Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  Min Distance Between Ground Floor Pedestrian  Min Distance Stephan State (siling Height or 50' Vertical Height (see note 3)  Alth Floor Ceiling Height or 50' Vertical Height (see note 3)  Alth Floor Ceiling Height or 50' Vertical Height (see note 3)  Alth Floor Ceiling Height or 50' Vertical Height (see note 3)  Alth Floor Ceiling Height or 50' Vertical Height (see note 3)  Alth Floor Ceiling Height or 50' Vertical Height (see note 3)  N/A  All Other Façade: residential: 30%; commercial: 10%	Rear	0'	<u> </u>	15' min.		
Other  Allowable Building SF  Front Façade: residential: 30%; commercial 60%  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required Tequired Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  Allowable Building 290,900 310,000 600  Front Façade: residential: 30%; commercial 30%  Rear Façade: Residential: 10% commercial: 15%  All Other Facades: Residential: none required Commercial: none required required  residential 100'; commercial 50'  residential 100'; commercial 50'	Stepbacks	4th Floor Ceiling Height or 50' Vertical	4th Floor Ceiling Height or 50' Vertical Height	N/A		
Allowable Building SF  Pront Façade: residential: 30%; commercial 60%  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required Commercial: none required Thomas Petween Ground Floor Pedestrian  MIN Distance Between Ground Floor Pedestrian  Allowable Building 290,900  310,000  Front Façade: residential: 30%; commercial 30%  Rear Façade: residential: 10% commercial: 15%  All Other Facades: Residential: none required Commercial: none required  Tesidential 100'; commercial 50'  residential 100'; commercial 50'	Frontage Build-out	70% min.	N/A	N/A		
Front Façade: residential: 30%; commercial 60%  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required Transparency MIN  MIN Distance Between Ground Floor Pedestrian  Front Façade: residential: 30%; commercial: 10% commercial: 10% commercial: 10% Commercial: none required  residential 100'; commercial 50'  residential 100'; commercial 50'	Other					
Ground Floor Transparency MIN  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required Transparency MIN  MIN Distance Between Ground Floor Pedestrian  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required Tresidential: 30%; commercial: 10% commercia		290,900	310,000	600		
Entrances	MIN Distance Between Ground Floor Pedestrian	residential: 30%; commercial 60%  Rear Façade: Residential: 10% Commercial: 15%  All Other Facades: Residential: none required Commercial: none required residential 100';	residential: 30%; commercial 30%  Rear Façade: residential: 10% commercial: 15%  All Other Facades: Residential: none required Commercial: none required residential: 100';	N/A		
Lot Coverage 90% Max. 90% Max 10% Max		90% Max	90% Max	10% Max		

#### Notes to Table D:

- 1.) Porches, eaves and awnings are considered to be part of the structure and shall not encroach into the minimum setback.
- 2.) Non-residential square footage allowed in neighborhood greenspace to accommodate structures such as picnic pavilions and structures accessory to the recreational use of the block.
- 3.) The rear façade of any building in Block 2 shall not extend more than 50' vertical height without a 15' stepback, where the rear façade height is the average height of three equidistant points measured from grade along the rear façade. This stepback is a rear a façade stepback.
- 4.) Front setback for Block 1 shall be measured from the edge of the future ROW dedication line for Rio Road W as shown on Sheet 7 of the Application Plan.
- 5.) Frontage build-out is measured as the portion of the front setback line that must be occupied by a structure.
- 6.) Lot Coverage is the amount of impervious surfaces permitted in each block.
- 7.) Buildings within the NMD shall be constructed in accordance with all applicable USBC standards, including building separation.